



$\frac{d}{dt} \left( \frac{1}{\sqrt{1-v^2/c^2}} \right) = \frac{v}{c^2} \frac{dv}{dt}$

[0004] For single slice CT systems that employ simple reconstruction weighting schemes, the scanning operators typically utilize the helical pitch of the scan as an indication of expected artifact. This can be difficult however for a new or inexperienced operator or for a CT system that has numerous operating modes. Furthermore, in multi-slice CT systems, with various pitch and detector width selections, an operator or technologist may find it very difficult to remember what to expect for each set of operating conditions.

[0005] Therefore, it would be desirable to design an apparatus and method that determines and visually displays a likelihood of artifact presence in a reconstructed image for evaluation by a scan system operator. Further, it would be desirable to design such a system that enables the system operator to provide feedback to the system such that artifact presence is reduced in a subsequent imaging session.

## Brief Description of Invention

[0006] An apparatus and process overcoming the aforementioned drawbacks is provided and includes determining and displaying a helical artifact index (HAI) to a system operator. The HAI is determined by acquiring and processing imaging data of a phantom. The HAI is then displayed to the operator on a console so that the operator may, if necessary, reset the scanning parameters or select a new scanning protocol that will result in a reconstructed image of a patient having reduced artifact presence. By providing a likelihood of artifact presence to the system operator, the present invention eliminates the need for the operator to recall those scanning profiles that are susceptible to high artifact presence.

[0007] Therefore, in accordance with one aspect of the present invention, a method of generating a helical artifact score is provided. The method includes acquiring a set of data values and setting a subset of the set of data values to an initial value. After setting the subset of data values to an initial value, the method includes filtering the set of data values. Next, a likelihood of artifact presence is determined from the filtered set of data values.

[0008] In accordance with another aspect of the present invention, a computer-readable

medium having stored thereon a computer program that, when executed by one or more computers, causes the one or more computers to acquire imaging data of a phantom from an external device. The imaging data includes a plurality of pixels. The computer program further causes the one or more computers to isolate a first set and a second set of pixels and set one of the first set and the second set to an initial value. After setting one of the first set and the second set to an initial value, the computer program causes the one or more computers to filter the imaging data and determine a helical artifact index (HAI) therefrom. The computer program then causes the one or more computers to visually display the HAI on a console.

[0009] In yet another aspect of the present invention, a CT system is provided and comprises a rotatable gantry having an opening and a high frequency electromagnetic energy projection source to project high frequency energy toward an object. The CT system further includes a scintillator array having a plurality of scintillators to receive high frequency electromagnetic energy attenuated by the object. A photodiode array is provided having a plurality of photodiodes. The photodiode array is optically coupled to the scintillator array and is configured to detect light energy emitted therefrom. The CT system further includes a plurality of electrical interconnects configured to transmit photodiode outputs to a data processing system and a computer program to acquire and process data to determine a likelihood of an artifact risk presence in a reconstructed image. The computer of the CT system is further programmed to notify an operator of the determined likelihood.

[0010] Various other features, objects and advantages of the present invention will be made apparent from the following detailed description and the drawings.

## Brief Description of Drawings

[0011] The drawings illustrate one preferred embodiment presently contemplated for carrying out the invention.

[0012] In the drawings:

[0013] Fig. 1 is a pictorial view of a CT imaging system;

[0014] Fig. 2 is a block schematic diagram of the system illustrated in Fig. 1;

- [0015] Fig. 3 is a flow chart setting forth the steps of displaying a likelihood of artifact presence in a reconstructed image in accordance with the present invention;
- [0016] Fig. 4 is a flow chart setting forth the steps of determining a likelihood of artifact presence;
- [0017] Fig. 5 is a flow chart setting forth the steps of a scanning session in accordance with the present invention;
- [0018] Fig. 6 is a histogram correlating the assignment of artifact presence values by the process of the present invention versus artifact value assignment by skilled observers.

## Detailed Description

- [0019] The operating environment of the present invention is described with respect to a four-slice computed tomography (CT) system. However, it will be appreciated by those of ordinary skill in the art that the present invention is equally applicable for use with single-slice or other multi-slice configurations. Moreover, the present invention will be described with respect to the detection and conversion of x-rays. However, one of ordinary skill in the art will further appreciate, that the present invention is equally applicable for the detection and conversion of other high frequency electromagnetic energy.
- [0020] Referring to Figs. 1 and 2, an exemplary computed tomography (CT) imaging system 10 is shown as including a gantry 12 representative of a "third generation" CT scanner. Gantry 12 has an x-ray source 14 that projects a beam of x-rays 16 toward a detector array 18 on the opposite side of the gantry 12. Detector array 18 is formed by a plurality of detectors 20 which together sense the projected x-rays that pass through a medical patient 22. Each detector 20 produces an electrical signal that represents the intensity of an impinging x-ray beam and hence the attenuated beam as it passes through the patient 22. During a scan to acquire x-ray projection data, gantry 12 and the components mounted thereon rotate about a center of rotation 24.
- [0021] Rotation of gantry 12 and the operation of x-ray source 14 are governed by a control mechanism 26 of CT system 10. Control mechanism 26 includes an x-ray controller 28 that provides power and timing signals to an x-ray source 14 and a



acquired imaging data within + 40 CT numbers of an expected uniform material value. This is accomplished by measuring the mean for a region of pixels near the center of the phantom absent any visual artifact.

[0025] After the mask is filtered at 160, process 100 generates a helical artifact index (HAI) at 170 as will be discussed with particular reference to Fig. 4. The HAI is then displayed on a console at 180 whereupon process 100 ends at 190.

[0026] Referring to Fig. 4, an algorithm 200 for determining the HAI begins at 210 with the determining of a mean value of pixels within the mask at 220. The mean value of the pixels within the mask is then subtracted from the image at 230. At 240, the pixels outside the mask are then set to an initial value. In one preferred embodiment, the initial value is zero. This however is illustrative of only one preferred embodiment. That is, the present invention is applicable with non-zero initial values.

[0027] After the pixels outside the mask are set to an initial value 240, the imaging data acquired at 140, Fig. 3, is filtered, in a preferred embodiment, with a 5 x 5 Hanning kernel. An illustrative 5 x 5 Hanning kernel applicable with the present invention is set forth in the table below.

[0028] Table 1

[t1]

0.00000	0.00000	0.00000	0.00000	0.00000	0.00000	0.00000
0.00000	0.00694444	0.0208333	0.0277778	0.0208333	0.00694445	0.00000
0.00000	0.0208333	0.0625000	0.0833333	0.0625000	0.0208333	0.00000
0.00000	0.0277778	0.0833333	0.111111	0.0833333	0.0277778	0.00000
0.00000	0.00694445	0.0208333	0.0277778	0.028333	0.0069445	0.00000
0.00000	0.00694445	0.0208333	0.0277778	0.0208333	0.00694445	0.00000
0.00000	0.00000	0.00000	0.00000	0.00000	0.00000	0.00000

[0029] After the imaging data is filtered at 250, a standard deviation of the pixels within the mask is determined at 260. The standard deviation is determined by squaring the pixels within the mask, summing the squares, and dividing the sum by the total

number of pixels within the mask. At 270, the standard deviation is then multiplied by a scalar suitable to obtain a maximum score of 10 for the worst case of artifact presence in a reconstructed image and a minimum score of 1 for the best case of artifact risk over the set of parameters available to the user. Setting a worst case score to 10 and a best case score to 1 is illustrative of only one embodiment that may be used to ascertain an artifact risk value. That is, a best case score of 10 and a worst case score of 1 or any variation thereof is contemplated herein and is within the scope of the present invention. Process 200 then ends at 280 with the visual displaying of the artifact risk value, in a preferred embodiment, as a visual bar graph on a scan Rx console at 180 of Fig. 3 as was heretofore discussed.

[0030] Referring to Fig. 5, algorithm 300 sets forth the steps of an acquisition, pre-processing, and reconstruction process in accordance with the present invention. Algorithm 300 begins at 310 with the selection of a scanning protocol at 320. Once the appropriate protocol is selected at 320, scan parameters are identified and selected at 330 that satisfy the requirements of the prescribed imaging session. Imaging data is then acquired and processed of a phantom at 340 whereupon an HAI index is determined at 345 in accordance with acts 110–190 of process 100, Fig. 3. The determined HAI is then evaluated by the system operator at 350 to determine if the implemented protocol selected at 320 is acceptable 360. That is, if the HAI indicates a high likelihood of artifact presence and such a presence is unacceptable, the operator may determine at 360 that the protocol is unacceptable. However, if the artifact presence is low or that a high artifact presence is tolerable, the operator may determine that the protocol selected and implemented at 320 is acceptable.

[0031] If the protocol is acceptable 360, 366, the pre-processing process is complete and a scan of a patient using the acceptable protocol is executed at 370 whereupon algorithm 300 concludes at 380 with the reconstruction of an image. However, if the system operator determines at 360 that the protocol was not acceptable 386, the pre-processing process continues at 390 with a revising of the protocol at 390. Revising the reconstruction protocol allows the system operator to alter the reconstruction algorithm used to process the data or select new scan parameters at 330 that will facilitate image reconstruction with minimal artifact presence. Once the protocol is revised at 390 and, if necessary, new scan parameters are selected at 330, pre-

processing continues at 340 with the acquisition and processing of data of a phantom and subsequent HAI determination and evaluation at 345 and 350. These pre-processing steps continue until an acceptable protocol is determined at 360. That is, regeneration of an HAI during pre-processing allows the system to provide visual feedback in the form of a bar graph to the operator so that a correct protocol may be selected and implemented.

[0032] Referring to Fig. 6, a histogram illustrating a comparison of artifact score assessment of the process of the present invention versus artifact score assessment by human observers is shown. That is, a set of helical body phantom images were evaluated using the helical artifact index generation process of the instant application. Those images were then presented to a set of skilled observers who were asked to sort and grade the images on a scale of 1 to 10 ranging from best to worst. As shown in Fig. 6, the artifact index generation process of the instant application scored the images in the same sequence as the skilled human observers thereby confirming that the helical artifact index generation process of the instant application correctly assigned index values to the images presented to the skilled observers.

[0033] Therefore, in accordance with one embodiment of the present invention, a method of generating a helical artifact score is provided. The method includes acquiring a set of data values and setting a subset of the set of data values to an initial value. After setting the subset of data values to an initial value, the method includes filtering the set of data values. Next, a likelihood of artifact presence is determined from the filtered set of data values.

[0034] In accordance with another embodiment of the present invention, a computer-readable medium having stored thereon a computer program that, when executed by one or more computers, causes the one or more computers to acquire imaging data of a phantom from an external device. The imaging data includes a plurality of pixels. The computer program further causes the one or more computers to isolate a first set and a second set of pixels and set one of the first set and the second set to an initial value. After setting one of the first set and the second set to an initial value, the computer program causes the one or more computers to filter the imaging data and determine a helical artifact index (HAI) therefrom. The computer program then causes



the one or more computers to visually display the HAI on a console.

[0035] In yet another embodiment of the present invention, a CT system is provided and comprises a rotatable gantry having an opening and a high frequency electromagnetic energy projection source to project high frequency energy toward an object. The CT system further includes a scintillator array having a plurality of scintillators to receive high frequency electromagnetic energy attenuated by the object. A photodiode array is provided having a plurality of photodiodes. The photodiode array is optically coupled to the scintillator array and is configured to detect light energy emitted therefrom. The CT system further includes a plurality of electrical interconnects configured to transmit photodiode outputs to a data processing system and a computer program to acquire and process data to determine a likelihood of an artifact risk presence in a reconstructed image. The computer of the CT system is further programmed to notify an operator of the determined likelihood.

[0036] The present invention has been described in terms of the preferred embodiment, and it is recognized that equivalents, alternatives, and modifications, aside from those expressly stated, are possible and within the scope of the appending claims.